



GRP Grating - 30 mm

**FLEXI-GRP-K530-38-5-GREEN**



Flexi Riste A/S  
Hjejlevej 10  
DK - 7480 Vildbjerg  
(+45) 97 13 32 11  
mail@flexiriste.dk  
www.flexiriste.dk

## FLEXI-GRP-K530-38-5-GREEN

### Properties

Matrix .....	Orthophtalic
Reinforcement .....	E-Glass
Colour .....	green, near RAL 6010
Height .....	30 mm
Surface .....	concave
Width of bars .....	5,00 – 6,50 mm
Pitch (C/C) .....	38,10 x 38,10 mm
Meshwidth .....	31,60 x 31,60 mm
Standard panel size .....	1226 x 3665 mm

### Tolerances:

Length / width .....	+ 0 / - 4 mm
Height .....	+ 1 / - 1 mm

### Fixing possibilities:

Clamp fixing .....	B138T / K
Direct .....	B638T / K

We supply all fixings for GRP gratings in galvanized steel, stainless steel AISI304 and stainless steel AISI316

### Mechanical properties

Weight .....	14,47 kg/m <sup>2</sup>
Matrix content .....	ca. 68 %
Glassfiber content .....	ca. 32 % (DIN 1172)
Density .....	1,8 kg/dm <sup>3</sup>
Serration class .....	R13 V10 (DIN 51130 og ASR A1 1.5/1,2)
E-Modulus .....	14.500 MPa (DIN EN ISO 178)
Max. bending stress .....	216 MPa
Area moment of inertia / 1 bar .....	12864,13 mm <sup>4</sup>
Section modulus / 1 bar .....	821,88 mm <sup>3</sup>

### Thermal properties

Max. application temperature .....	- 30°C / + 70°C
Flammability .....	Bfl-s1 (DIN EN 13501-1)
Flammability regarding UL94 .....	V-0 (DIN IEC EN 60695)

### Electric properties

Leak resistor .....	electrically non-conducting
---------------------	-----------------------------